


ASUS ROG Loki SFX-L 850W Platinum White power supply unit 24-pin ATX Wit

Merk : ASUS

Productfamilie: ROG

Artikelcode: 90YE00N2-B0NA00

Productnaam : Loki SFX-L
850W Platinum White



ASUS ROG Loki SFX-L 850W Platinum White. Totaal vermogen: 850 W, AC invoer voltage: 100 - 240 V, Gecombineerd vermogen (+3.3V): 110 W. Motherboard power connector: 24-pin ATX, Motherboard power cable length: 45 cm, SATA power cable length: 600 mm. Bedoeld voor: PC, Power supply unit (PSU) form factor: SFX-L, 80 PLUS certificatie: 80 PLUS Platinum. Kleur van het product: Wit, Type koeling: Actief, Ventilator diameter: 12 cm. Breedte: 125 mm, Diepte: 125 mm, Hoogte: 63,5 mm



Energie		Poorten & interfaces	
Totaal vermogen *	850 W	CPU power connector (4+4 pin)	✓
AC invoer voltage *	100 - 240 V	Lengte CPU-stroomkabel	55 cm
Gecombineerd vermogen (+3.3V)	110 W	Bekabelingstype	Volledig modulair
Gecombineerd vermogen (+12V)	850 W	Prestatie	
Gecombineerd vermogen (+5V)	110 W	80 PLUS certificatie *	80 PLUS Platinum
Gecombineerd vermogen (-12V)	9,6 W	Supported motherboard form factors	ATX
Gecombineerd vermogen(+5Vsb)	12,5 W	Bedoeld voor *	PC
Max huidige output (+3.3V)	20 A	Vormfactor van de voeding (PSU) *	SFX-L
Max huidige output(+12V)	70,8 A	Bearing technologie	Kogellager
Max huidige output (+5V)	20 A	Design	
Max huidige output (-12V)	0,8 A	Kleur van het product	Wit
Max huidige output (+5Vsb)	2,5 A	Type koeling	Actief
Stroomspanning bescherming	Te hoog vermogen, Overspanning, Overbelasting, Oververhitting, Kortsluiting, Onder spanning	Ventilator diameter	12 cm
Poorten & interfaces		Aantal ventilatoren	1 ventilator(en)
Motherboard power connector *	24-pin ATX	Belichting	✓
Lengte stroomkabel moederbord	45 cm	Aan/uitschakelaar	✓
Aantal SATA power connectors	6	Gewicht en omvang	
Lengte SATA-stroomkabel	600 mm	Breedte	125 mm
Peripheral (Molex) power connectors (4-pin) *	4	Diepte	125 mm
Lengte stroomkabel randapparaat (Molex)	600 mm	Hoogte	63,5 mm
PCI Express power connectors (8-pin)	3	Gewicht	1,81 kg
PCI Express-voedingsconnectoren (16-pins)	1	Verpakking	
Lengte PCI Express-stroomkabel	45 cm	Breedte van de verpakking	285 mm
		Diepte van de doos	190 mm
		Hoogte van de verpakking	100 mm
		Gewicht pakket	2,5 kg
		Verpakkingstype	Pak
Technische details		Naleving van duurzaamheid	✓
		Certificaten van naleving	RoHS



4711081722229

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 31-OCT-2024. Prints or copies of Information are only valid on the printed Publication date