

ASUS ROG -STRIX-850P-GAMING power supply unit 850 W 20+4 pin ATX ATX Zwart

Merk : ASUS

Productfamilie: ROG

Artikelcode: 90YE00W2-B0NA00

Productnaam : ROG-STRIX-850P-GAMING

ASUS ROG -STRIX-850P-GAMING. Totaal vermogen: 850 W, AC invoer voltage: 100 - 240 V, Power Factor Correctie (PFC) type: Actief. Motherboard power connector: 20+4 pin ATX, Motherboard power cable length: 61 cm, SATA power cable length: 400,120 mm. Bedoeld voor: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certificatie: 80 PLUS Platinum. Kleur van het product: Zwart, Type koeling: Actief, Aantal ventilatoren: 1 ventilator(en). Meegeleverde kabels: CPU, PCIe, SATA, Peripheral (Molex)



Energie		Poorten & interfaces	
Totaal vermogen *	850 W	CPU power connector (4+4 pin)	✓
AC invoer voltage *	100 - 240 V	Lengte CPU-stroomkabel	100 cm
Power Factor Correctie (PFC) type	Actief	Prestatie	
Gecombineerd vermogen (+3.3V)	130 W	80 PLUS certificatie *	80 PLUS Platinum
Gecombineerd vermogen (+12V)	850 W	Bedoeld voor *	PC
Gecombineerd vermogen (+5V)	130 W	Vormfactor van de voeding (PSU) *	ATX
Gecombineerd vermogen (-12V)	3,6 W	ATX version	3.1
Gecombineerd vermogen(+5Vsb)	15 W	Stille modus	✓
Max huidige output (+3.3V)	25 A	Mean time between failures (MTBF)	120000 uur
Max huidige output(+12V)	70,8 A	Design	
Max huidige output (+5V)	25 A	Kleur van het product	Zwart
Max huidige output (-12V)	0,3 A	Type koeling	Actief
Max huidige output (+5Vsb)	3 A	Aantal ventilatoren	1 ventilator(en)
Stroomspanning bescherming	Overstroom, Te hoog vermogen, Overspanning, Oververhitting, Kortsluiting, Onder spanning	Ventilator locatie	Boven
Poorten & interfaces		Inhoud van de verpakking	
Motherboard power connector *	20+4 pin ATX	Meegeleverde kabels	CPU, PCIe, SATA, Peripheral (Molex)
Lengte stroomkabel moederbord	61 cm	Gewicht en omvang	
Aantal SATA power connectors	6	Breedte	160 mm
Lengte SATA-stroomkabel	400,120 mm	Diepte	150 mm
Peripheral (Molex) power connectors (4-pin) *	3	Hoogte	86 mm
Lengte stroomkabel randapparaat (Molex)	400,150 mm	Gewicht	1,78 kg
PCI Express power connectors (6+2 pin)	3	Verpakking	
PCI Express-voedingsconnectoren (16-pins)	1	Breedte van de verpakking	320 mm
Lengte PCI Express-stroomkabel	75 cm	Diepte van de doos	200 mm
		Hoogte van de verpakking	108 mm
		Gewicht pakket	2,8 kg
		Verpakkingstype	Pak

Technische details

Certificaten van naleving

RoHS



4711387594520

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 20-OCT-2024. Prints or copies of Information are only valid on the printed Publication date